DO NOT OPEN THIS TEST BOOKLET UNTIL YOU ARE TOLD TO DO SO Booklet Serial No. 115957

Test Booklet Series

TEST BOOKLET ASSISTANT ENGINEER CIVIL

Written Test - 2023

(20)



Time Allowed: Two Hours

Maximum Marks: 120

INSTRUCTIONS

- IMMEDIATELY AFTER THE COMMENCEMENT OF THE EXAMINATION, YOU SHOULD 1, CHECK THAT THIS TEST BOOKLET DOES NOT HAVE ANY UNPRINTED OR TORN OR MISSING PAGES OR ITEMS, ETC. IF SO, GET IT REPLACED BY A COMPLETE TEST BOOKLET. 2,
- Please note that it is the candidate's responsibility to encode and fill in the Roll Number and Test Booklet Series Code A, B, C or D carefully and without any omission or discrepancy at the appropriate places in the OMR Answer /Response Sheet. Any omission/discrepancy will render the Response Sheet liable for rejection. 3.
- You have to enter your Roll Number on the Test Booklet in the Box provided alongside. DO NOT write anything else on the Test Booklet.

2003515

- This Test booklet contains 120 items (questions). Each item comprises of four responses (answers). 4. You will select the response which you want to mark on the Answer Sheet/Response Sheet. In case you feel that there is more than one correct response, mark the response which you consider the best. In any case, choose ONLY ONE response for each item. 5.
- You have to mark all your responses ONLY on the separate Answer /Response Sheet provided. See
- 6. All items carry equal marks.
- Before you proceed to mark in the Answer /Response Sheet, the response to various items in the 7. Test Booklet, you have to fill in some particulars in the Answer /Response Sheet as per instructions sent to you with your Admission Certificate.
- After you have completed filling in all your responses on the Response Sheet and the examination 8. has concluded, you should hand over to the Invigilator only the Answer /Response Sheet. You are permitted to take away with you the Test Booklet and Candidate's Copy of the Response Sheet .
- Sheets for rough work are appended in the Test Booklet at the end. 9.
- While writing Centre, Subject and Roll No. on the top of the Answer Sheet/Response Sheet in 10. appropriate boxes use "ONLY BALL POINT PEN".
- 11. Penalty for wrong answers:


THERE WILL BE PENALTY FOR WRONG ANSWERS MARKED BY THE CANDIDATE IN THE WRITTEN TEST (OBJECTIVE TYPE QUESTIONS PAPERS).

- There are four alternatives for the answer to every question. For each question for which a wrong answer has been given by the candidate, (0.25) of the marks assigned to that question will be deducted as penalty.
- If a candidate gives more than one answer, it will be treated as a wrong answer even if one of the (ii) given answers happens to be correct and there will be same penalty as above for that question.
- If a question is left blank, i.e., no answer is given by the candidate, there will be no penalty for (iii) that question.

DO NOT OPEN THIS TEST BOOKLET UNTIL YOU ARE TOLD TO DO SO

P.T.O.


Two bodies of masses m1 and m2 are hung from the ends of a rope, passing over a frictionless pulley as shown in Fig. below. The acceleration of the string will be:



5mg - T = 5ma T - 2mg - 2ma 3mg = 7r

- 3/7 gA)
- B) 4/7 g
- 7/2 g C)
- 2/7 g D)

- A steel wire of 20 mm diameter is bent into a circular shape of 10m radius. If the modulus 2. of elasticity is 2×106 kg/cm², then the maximum stress induced in the wire is:
 - 10^3 kg/cm2 A)
 - 2*10^3 kg/cm2 B)
 - 4*10^3 kg/cm2
 - D) 6*10^3 kg/cm2
- The shear force diagram of a beam is shown in the figure. The absolute maximum bending v3. moment in the beam is: (Assume moment at A is equal to zero)



- A) 4Pa
- B) 5Pa
- 6Pa C)
- 7Pa D)

4.	Wha ratio	at is the correct expression of bulk modulus (K), Modu	lus of rigidity (G) and Poisson's
	A)	μ =(3K-4G)/(6K+4G)	
	B)	$\mu = (3K + 4G)/(6K - 4G)$	
	C)	$\mu = (3K-2G)/(6K+2G)$	
	D)	μ =(3K+2G)/(6K-4G)	
5.		en a cantilever beam, is loaded at its free end, the maxi elop at:	mum compressive stress shall
	A)	Top fibre	
	B)	Bottom fibre	
	C)	Neutral axis	
	D)	Centre of gravity	
		- F - BIN C	3 T
6.		naft of 60 mm diameter is subjected to torsion has a sh wist will be equal to	near strain of 0.0006. The rate
	A)	0.00002	ib mire (11) to orive Isose A
	B)	0.0025th as besubri stress intended and the decidence	
	C)	0.0036	
	D)	0.00001	B) 2710/31/prin2
			(1 C) 4*10*3 kmcm2
<i>J.</i> /	A m	ild steel bar of uniform cross-section A and length 2L i total energy stored in the bar would be:	
	A)	(Assume moment at A is equal to zero) AAJA	
	B)	(P^2 L)/2AE	
	C)	PL/2AE	
	D)	(P^2 L)/AE	
_		her of independent elastic constant for a linear elasti	alasma,
8.	The	number of independent elastic constant for a linear elasti erial is	
	A)	1	
	B)	2	
	C)	3	
	D)	4	
•			D). The
(20)	(A)	(4)	(A)
			- 1997 - 1997年 - 199


- 9. In a plane strain in the xy plane, normal strain in x and y directions are equal to zero and shear strain is equal to 3×10^{-6} . What is the value of diameter of Mohr's circle of strain for these strain values?
 - A) 6 × 10⁻⁶
 - B) 3 × 10-6
 - C) 2×10^{-6}
 - D) 9 × 10-6
- 10. Considering the following:

Major principal stress $\sigma 1 = 150 \text{ N/mm}^2 \text{ (tensile)}$

Major principal stress σ2 is compressive.

What would be the value of $\sigma 2$ in N/mm² at which yielding will commence according to maximum shear stress theory, if the uni-axial tensile yield stress is 230 N/mm²?

- A) 50 Compressive
- B) 40 Tension
- C) 80 Compression
- D) 60 Tension
- Which of the following conditions is satisfied both in plastic and elastic analysis
 - A) Equilibrium condition
 - B) Yield condition
 - C) Mechanism condition
 - D) Plastic moment
 - 12. A brass bar of solid section is encased in a steel tube shown in figure. The coefficient of expansion of steel is 11.2 × 10⁻⁶ per °C and the coefficient of expansion of brass is 16.5 × 10⁻⁶ per °C. The composite bar is heated through 60 °C. Now consider the following statements:



The stress in the brass will be tensile

- i. The stress in the steel will be tensile
- ii. The stress in the brass will be compressive
- iii. The stress in the steel will be compressive

Which of the statements given above are correct?

- Ay i and ii
- B) i and iii
- C) ii and iv
- D) ii and iii


13. Castigliano's theorem comes under which one of the following method:

- Equilibrium method A)
- Displacement method B)
- Stiffness method C)
- Force method D)

14. The section modulus of a circular section about an axis through the centre of the C.G, is

- $(\pi d^2)/4$ A)
- $(\pi d^2)/16$ B)
- $(\pi d^3)/16$ C)
- $(\pi d^3)/32$ D)

15. The given figure shows a portal frame with one end fixed and other hinged. The ratio of fixed end moments M_{BA}/M_{CD} due to side sway will be:



- A)
- B)
- D)

16: According to IS 2212:1991 the nominal thickness of 11/2 modular brick wall is:

- A) 19 cm
- B) 29 cm
- 30 cm
- 40 cm


(20) (A)

17.	A sto	eel rod of 20mm	diameter has bee	n used as a tie l	pracing system, but may	he subjected
	men	aber?	of stress due to v	vind. What is the	oracing system, but may ne maximum permitted	length of the
	A)	1650 mm		19 Par 0 5	- maximum perimited	
	B)	1750 mm				
	C)	1850 mm				
	D)	1550 mm			rb lamosti la icaldilla	
	D)	1330 IIIM				
18.	A 00					
10.	ACC	ording to 12 10	77:1992 the com	mon burnt clay	bricks are classified o	n the basis of:
					Secretary Secretary	117: (0)
	B)	Marking				
	C)	Type of bond				
	D)	Average com	pressive strength	ü das ambasılır. V		
			s dat to load out			n them the co
19.	(6y 'M'.) up to depth of The magnitude	section of width h/4 from both the of the moment 'l	e top and botto	h' has been stressed up m face under the actio	to yield point n of a moment
	A)	10/24bh²σy				
	B)	1/4bh²σy	an or n sampar ais	aleabhoo paois		faltan na regi
	C)				' diak	
	D)	13/36bh ² σy			36_05)):0x2 - (4):1
20.	dire A) B)	ect compression 10 8	n (N/mm²) :	te pylesog nosi	ress in M30 grade of	TO S 2807 Fullet Hem
	C)	9				
: :	D)	11.5	so na súbabblocha Tagairtí	obered grade	er 16. 4562,000 the mi Assemblereed concrete	IJA According
21.		mponent such a	s a beam end pla		result of the flexing angle.	of a connection
		The state of the s				
	B)	Chaor force			e l'és es deconspacrion	
	C)				odr libratours blen in	
	D)	Bending for	00 011 0011		is no a likeblacing	
22.	pr tha M	obability that a an 5 Mpa. Deter pa):	s to be designed in individual cube mine target mea	for a strength e strength test n strength, (Co	n of 35 MPa, such the result will fall below? onsider standard devia	at there is a 5% 35 MPa by more ation for mix as 4
	A)	36.6 Mpa				
	B)					
	· C)	34 Mpa	2,3 and 4 are, a			
	D)	and the latest from	All are correct	(C)	James one I	tan E. t. (5 -
	-,			(5)		m o
(20) (A)	<u>4</u>)		(7)		[P.T.O.

C

23 .	Pl 1.	hysical properties of structural steel irrutural Unit mass of steel $\rho = 7850 \text{ kg/m}$ 3	espec	ctive of its grad			S: /
	2.	Modulus of elasticity $E = 2.0 \times 10^{\circ}$	5 N/n				
	3.	Poisson ratio $= 0.3$	- 0, -	····· (mpa)	mir! (
	4.	Modulus of rigidity $G = 0.769 \times 10^{-10}$)5 N/r	nm²(mna)			
	5.	Co-efficient of thermal expansion of	$\alpha = 1$	2 × 106/9C	HMI S		
		noose correct option from the codes give					
	A		CII U	Clow			
	B)						
	C)						
	D)						
	2,	rediction above			31164		
34 .		e maximum value of effective slenderr mber in which a reversal of direct stress ce is	iess r occui	ratio (As per IS rs due to loads o	800 : 2007) ther than wir	for a t	tension seismic
	A)	350	R)	250		5	
	C)	180		250 400			
			D)	400			
25,	Inv	working stress design of reinforced con- expression:	crete	etmiotimos the	2.000		
	the	expression:	crete	structures the m	lodular ratio	is giv	en by
	A)	280/(3σ_cb)					
	B)	280/(3σ_cc)					
	C)	280/(3σ_cu)					
	D)	280/σ_cc					20.
	Not	e: Here σ_{cb} and σ_{cc} is the compression of the substant σ_{cc} is the substant σ_{cc}	ive st	ress in hending	ond diameter		
	resp	pectively and σ_cu is the ultimate comp	ressiv	ve strenoth	and direct co	mpre	ssion
•							
26.	Acc	ording to IS 456:2000 the minimum gradition for reinforced congrets.	rade o	of concrete in c	ase of sever)
		Thorca Contract					
	A)	M20 M30	B)	M25			
	C)	M30	D)	M40			.11
27	0						
27.	Con	sider the following statement regarding In bolted/riveted construction	the L	acing bars			
	1.	In bolted/riveted construction, the minimum the nominal diameter of the end bolt ri	mum	width of facing t	oars shall be f	our tir	nes
	2.	The thickness of flat lacing bars shall a	not be	e less than one-f	ortieth of its	affaat	
	E PI	single lacings and one-sixtle	th of t	ne effective leng	th for double	lacin	-
20,140	3.	of equivalent	stren	gth may be pern	nitted instead	of fl	gs.
		racings					
	4.	Lacing bars, whether in double or single	le sys	tems, shall be in	clined at an a	ingle i	not
	Choc	less than 40° nor more than 70° to the ose correct option from the codes given	helor	or the built-up n	iember.		
	A)	Jare Correct	B)	2 3 and 4 are a	22 4 Myd.	(8)	
	C)	I sand 4	D)	2,3 and 4 are co	rect	0	
(20) (A)	Collect	D)	All are correct	26 2,100	(G.	
		(8)				(A)	(20)

28) Determine the depth of neutral axis for the section shown in figure. Assume σck = 25 Mpa, σy = 415 Mpa and cover 40mm.



- A) 100mm
- B) 90mm
- C) 96.8mm
- D) 320mm

25. Gantry girders are design to resist:

- 1. Lateral loads
- 2. Longitudinal loads
- 3. Vertical loads
- A) 1, 2 and 3
- B) 1 and 2
- C) 1 and 3
- D) 2 and 3

30. If ϕ is the dia of the plain bar in compression and σ st is the stress in the bar. Determine the development length of the bar, bond strength of concrete is τ bd.

- A) $\frac{\phi.\sigma_{st}}{4\tau_{bd}}$
- B) $\frac{\phi.\sigma_{st}}{8\tau_{bd}}$
- $C) \quad \frac{\phi.\sigma_{st}}{6.4\tau_{bd}}$
- D) $\frac{\phi.\sigma_{st}}{5\tau_{bd}}$

Assertion: At the standard temperature, the value of the Kinematic viscosity of water comes out to be lower than that of air at similar temperature.

Reasoning: At the standard temperature, the value of the dynamic viscosity of water comes out to be lower than of air at similar temperature.

- A) Both A and R are true and R is the correct explanation of A.
- B) Both A and R are true but R is not the correct explanation of A.
- C) A is true but R is false.
- D) A is false but R is true.
- 32. Velocity distribution of fluid flow over a flat plate is given by equation 3+ 0.5y -y² (where y is the vertical distance from the plate surface). Select the correct value of shear stress at a vertical distance of 0.2 m if the dynamic viscosity of the fluid is 0.7 N-s/m²
 - A) 0.14 N/m²
 - B) 0.07 N/m²
 - C) 0.1 N/m^2
 - D) 0.28 N/m²
- 33. An air bubble (diameter 50 mm) inside a water bucket have pressure 4.5 N/m² more than the surrounding pressure. Then the force inhibiting the bubble from bursting is given by?
 - A) 0.028 N/m
 - B) 0.056 N/m
 - C) 0.0625 N/m
 - D) 0.1 N/m
 - 34. A Newtonian fluid of relative density 0.45 is held back by a vertical gate of dimension (6×6) m with free surface of fluid at its top. Find the moment of the force exerted by the fluid with respect to the bottom edge of the gate (z is the specific weight of water):
 - A) 72 z
 - B) 97.2 z
 - C) 216 z
 - D) 16.4 z
- 35. Velocity potential function for a fluid flow condition is given as $3x^2 + 4y^2$, calculate the magnitude of velocity at (1,1)?
 - A) 7 units
 - B) 100 units
 - C) 10 units
 - D) 25 units

(A) (US)

36. Which	th of the following at		
1	ch of the following statements are con Flow is irrotational	nsidered in Bernoulli's assumptions:	
2.	Flow is incompressible	State of the commence of the c	
3.	Viscous force is ignored		
4.	Flow is considered steady	The state of the s	
A)	2,3 and 4		
B)	2 and 4	getti	
C)	1, 2 and 4	Hells	
D)	1,2,3 and 4	ch one of the To Jawing statements :	Will Whi
37. Find x+x	the stagnation point for a fluid flow y + 3 while velocity in Y direction (v)	condition where velocity in X direct	ion (u) is
A)	(2,-5)		
B)	(-2,-5)		
C)	(25)	and a design and the second party of the second	
D)	(2,5)	A lodels are nivery's smaller three from	
	a it species. The action of the following was	ha i sait hann wall tannin saire a sair	Ag Com
whe	n the options given below the select on bath tub is emptied through a central	[1] [1] [1] [1] [1] [1] [2] [1] [1] [1] [1] [1] [1] [1] [1] [1] [1	observed
A)	Rotational vortex	Water for all wall brondese as conjugate	
B)	Rankine vortex	Water fevel will remain sains	(8)
C)	Free vortex flow	Variation of the eron error arthurst	
D)	Forced vortex flow	Water les J. of Names and a first filler	
Dia	o reservoirs with different water levels meter of pipe A is twice than that of p	are connected by two pipes A and B i ipe B. The ratio of frictional loss in p	in parallel. ipe B than
	t of pipe A comes out to be?		
A)	2	Alexander	
B)	1	10 m²/s	
C)	4	76m2/s	
D)	32	olym I	
40. W	hich one of the following statements		
1.	to increase in local velocity.	sure level drops below the vapour pr	essure due
2.	Cavitation takes place in turbine bl		
3.	Cavitation can be prevented by in elevation level of the section unde	ncreasing the ambient pressure by	raising the
20015V		educed by providing covering of sta	inless stool
4.	and rubber etc.	and any providing of sime of sime	micss steel
A)		in the second second	
→ B)		4. (b. 2. Cost the)	
C)		-3 6-2 0-4 6-1	
D)		\$ \$ debuc-0 \$-0 1-	
(20) (A)		(11)	[P.T.O.
V-1/ (-)		기가 있다면 이번 사용하다 중요점	

41.	If	$m = total$ number of variables and $n = total$ number of π terms in Buckingham's	number of fundamental dimensions	involved
			will method would be:	
	A)	m+n	Viscous force is functed and	
	B)	(m-n) +1	Vlaces broshisaansi wafe	. L
	C)	m×n	2,3 and 4	GA.
	D)	m-n		
α	****		1. 2 and 4	
42		nich one of the following statements is		
	A)	Dynamic similarity between a mod Reynolds number in a viscous flow.	del and prototype can be verified by	equating
	B)	Mach number achieves significance the sonic velocity.	when the velocity of fluid approaches of	or exceeds
	C)	Distorted models are always exagge	erated on a vertical scale.	
	D)	Models are always smaller than the		
				(D)
43.	sect	nsider a subcritical flow condition in a tion is suddenly increased then what wil sume no choke condition)?	rectangular open channel, when the label the impact on the water level in the	e width of the channel
	A)	Water level will increase as compar	ed to the previous value	
	B)	Water level will remain same	Kangroevortos	
	C)	Water level will drop as compared to	o the previous value	
	D)	Water level will increase first then i		
		ere consected by two pipes A and E in	reservoirs with different water levels	35 Two
44.	-	pillway having a discharge of 7 * 10 ⁵ e of 1:100. The discharge required in		tory on a
	A)	$7 \text{ m}^3/\text{s}$		
	B)	10 m ³ /s		
	C)	70m ³ /s		0 30
	D)	1 m ³ /s	28.	
45.	Mat		ch one or the following statements a	40. Whi
	Iviat		List- II (Characteristics)	
		List -I (Type of turbine)		
	a.	Pelton turbine 1.		2.
	b.	Kaplan turbine 2.		
	C.	Propellor turbine 3. Francis turbine 4.		
	d.		Axial flow reaction with fixed var	nes
	A)	a-2 b-3 c-4 d-1		(A]
	B)	a-1 b-2 c-4 d-3		
	C)	a-3 b-2 c-4 d-1	2, 3 and 4	
	D)	a-1 b-2 c-3 d-4	A brun 1	(d
(20)	(A)	(1)	2)	(A) (DS)

6. The U	Inified	soil a	lacci	Garde					
A)	Grain s	hane	14351	ilcation s	ystem (USCS) for the soil class	sification is base	ed on	V
	Grain to	_							
	Gradati								
	Grain l		,						
Σ,	Orani i	ongu						(0)	
7 The v	oid rat	io (e)	and	porosity	(m) - C				
A)	0 <n<1< td=""><td>e>0</td><td>) and</td><td>porosity</td><td>(n) of so</td><td>011 1S</td><td></td><td></td><td></td></n<1<>	e>0) and	porosity	(n) of so	011 1S			
B)	n>0, e	, o o >0	yran.	tion is 20	nsolida	layer to achieve 90 % co	curre for a clay		
C)	n<1, e				Lan To	Hidarion in the clay laye			
D)	n<1, e						2 [∆] years		
D)	11-1, 0	-0					5 years		
9/ The	coturate	d un	it wa	ight of so	il ic 20	kN/m³, rw of water is 1	0 kN/m ³ and the		c
						atio of soil is	o Ki vili dila di	(LI	
A)	0.85	1. VII	Palaad	Internation	of other	eg required to be placed)	surchards hadis	X The	8
B)	0.65					agreement of the place and supplements and the supplement of the s			4
C)	0.25						2¢/Vk		
D)	0.45								
A) B)	45 % 65.3 °	%				statements from the foll zone water is under ten	In the capiliary		
C)	57.1	%	and provide the	- s micros	anh at l	permeability test is used	Constant board		
D)	83.7	%		zg zamu. coverbaith	hipher	esser permeability gives			
		10 10				e correct answer:		.vi	
50. Ma			id list	: - 11 and s	select un	List - II	iii bacı		
	List		do opr	orotus	1.	Specific gravity	ii and iii		
a. b.			ter te	aratus st	2.	Maximum dry density	and optimum n	noisture	,
						content	and ivoid basi	(3	
c.	Dire	ct sh	ear te	st	3.	Liquid limit			
n. old						Cohesion and angle of			
naine Co	odes:		01/6	noshodr		ratio of average permea			
	a	b	C	d					
A)	4	3	2	1			8/7		
B)		2	3	1 :					
C)		1	4	2					
. D)		4	2	1					
(20) (A)						(13)		[P.T	.0.
(-0) (11)	1.5		Q	1. V - 12		1.00		(4.3)	

51.	For	For a saturated soil deposit with vold ratio 0.7 and spec gradient is:	ific gravity 2.7, the critical hydraulic
	A)		
	B)	3) 0.5	
	(C)		
	D)		
,52°.	The	The time for a clay layer to achieve 90 % consolidation in the clay layer of half t	on is 20 years. The time required to hickness is
	A)	O 20 years	
	B)	3) 5 years	
	C)	c) 10 years	
	D)	7.5 years	Carulyjus dear keipsotes saft (1997) Ustostol fiolius (21.) talvassa –
53 .	The retai	he surcharge loading required to be placed on the hor etaining wall to completely eliminate tensile crack	izontal backfill of a smooth vertical
	A)		
	B)	3) 2c√k,	
	C)	() 2c	
	D)		la di Primeri da Abrahado estr. Militar praticora completa altr
54.	Cho	hoose the correct statements from the following	
	i.	In the capillary zone water is under tension	나 많은 하시 하셨다. 여름, [1]
	ii.		mine permeability is also
	iii.	i. A soil having lesser permeability gives higher d	ischarge
	iv.	The effective stress increases due to capillary z	one
	A)		And it is a property of the party of the par
	B)) ii and iii	
	C)		
	D)		
	,	Levil Lings	
55.	unck	a 3 layered soil deposit the permeability ratio is 1: ickness. What is the ratio of average permeability in layers?	2:4. The soil deposit is of uniform horizontal to vertical stratification
	A)	8/7	
	B)	12/15	
	C)	49/36	
	D)	7/15	
(20) ((A)	(14)	e-kip

	Dete	rmine the l	enotl	h of pile (N	apacity of pile	is 1000 kN.	s clay soil having t The adhesion fac	tor is	0.5.
	A)	17.75 m	ogu	or bue (M	=9)				
	B)	8.32 m							
	C)	10.5 m					Bullet test		
	D)	22.56 m					Kelly ballitest		
	υ,	22.30 III							Sex
57.	The	unconfined	d con	apressive str	rength of a cla	vev soil is 8	0 kPa, the undrain		
	A)	80 kPa					A stone with larg		
	B)	20 kPa					All of the sbove	D)	
	C)	40 kPa				*			
	D)			ick after im	of the class br	(by weight)	water absorption o		(10)
58.		The state of the s					nd 20 % respective and activity of cla	5.5.5	ven
	A)	30 and 5					25%	()	
	B)	40 and 4					15%		
	C)	50 and 6							
500	D)	30 and 3					offective length of and these buttesse		64.
			111544			OUT HOO KE	(29225		
59.	Picl	k the odd or	ne ou	t			0.81		
	A)	Geonet					1.6.0		
							100		
	B)	Geogrou	t		· ' ' ,		2.01		
,		Geogrou Geocell	t		•		10.L		
	B)	Geocell Geogrid							
ni j	B) C) D)	Geocell Geogrid			uncontrolled a	d by due to			20)
69.	B) C) D)	Geocell Geogrid	owing	3			1.0 L ch defect is cause d		(3)
69.	B) C) D) Ma	Geocell Geogrid atch the follo	owing cal M	3	1.	Prefabrio	J 0. 1	idW cow	a
60 .	B) C) D) Ma a. b.	Geocell Geogrid atch the follo Mechani Grouting	owing cal M	g lethod	1. 2.	Prefabrio Vibrocor	cated vertical drain	D) Wood A) at	<u>(a)</u>
60 .	B) C) D) Ma a. b. c.	Geocell Geogrid atch the follo Mechani Grouting Hydrauli	owing cal M	g lethod dification	1. 2. 3.	Prefabrio Vibrocor Geogrid	cated vertical drain	idW cow	<u>(3)</u>
69 .	B) C) D) Ma a. b. c. d.	Geocell Geogrid atch the follo Mechani Grouting Hydrauli Reinforc	owing cal M	g lethod dification	1. 2.	Prefabrio Vibrocor Geogrid	cated vertical drain	D) Wood A) at	3
60 .	B) C) D) Ma a. b. c. d.	Geocell Geogrid atch the follo Mechani Grouting Hydrauli Reinforce des:	owing cal M	g lethod dification nt	1. 2. 3. 4.	Prefabric Vibrocor Geogrid Cement	cated vertical drain	idW woow A) as (B) (C) (C)	
60 .	B) C) D) Ma a. b. c. d. Co	Geocell Geogrid atch the following Grouting Hydrauli Reinforce des: a b	owing cal M ic mode emen	g lethod dification nt	1. 2. 3. 4.	Prefabric Vibrocor Geogrid Cement	cated vertical drain	idW woow A) as (B) (C) (C) (C) (C)	
-60.	B) C) D) Ma a. b. c. d. Co	Geocell Geogrid atch the follo Mechani Grouting Hydrauli Reinford des: a b 1 3	owing cal M	g lethod dification nt	1. 2. 3. 4.	Prefabric Vibrocor Geogrid Cement	cated vertical drain mpaction	D) wood wood A) 21 B) C) C) C) C) College Foot	
60.	B) C) D) Ma a. b. c. d. Co A) B)	Geocell Geogrid atch the follo Mechani Grouting Hydrauli Reinford des: a b 1 3 4 2	owing cal M ic mode emen	dification d d d d d	1. 2. 3. 4.	Prefabric Vibrocor Geogrid Cement	cated vertical drain mpaction	(Q) woow (A) (B) (C) (C) (C) (C) (C) (C) (A) (A) (B)	
60 .	B) C) D) Ma a. b. c. d. Co	Geocell Geogrid atch the follo Mechani Grouting Hydrauli Reinford des: a b 1 3	owing cal M	g lethod dification nt	1. 2. 3. 4.	Prefabric Vibrocor Geogrid Cement	cated vertical drain mpaction	D) wood wood A) 21 B) C) C) C) C) College Foot	

	نشد ا	ne strength of concrete in hardened existing structure following tests	•					
6	i. Th	e strength of concrete in hardened existing struction	ire ca	in be d	eterm	ined	by w.L	
•	uno	Cons penetration test					-2 MU	ich of
	A)	-						
	B)							
	C)							
	D)	Kelly ball test						
63	1171	ish of the following statements is arrong						
62		nich of the following statements is wrong						
	A)	Quartz has a greasy lusture.						
	B)	Feldspar is a silicate of aluminium with varying A stone with large percentage of quartz is very a	amo	unts of	potas	h, soo	da or i	ine .
	C)	S I S T T T T T T T T T T T T T T T T T	oft		0.1	7.1 (5)		mué'
	D)	All of the above						
63	The	water absorption (by weight) of first class brick anours	after	immer	sing i	n col	d	
					Sing I	ii col	u wate	er for
	A)	30%						
	B)	20%	Suci	alg bru	Jimil.			
	C)	25%	HOBE					
	D)	15%						
64.	The	effective length of masonry wall stiffened by buttre	2622	on hot	on de	\$0.8t	0	
	-	are be detiresses at bour ends is (1, 1s the c/c leng	th of	the wa	ll bets	and	contin	uing
	buttr	esses)	uror	uic wa	II DELV	veen	succes	ssive
	A)	0.8 L						
	B)	0.9 L						
	C)	2.0 L			tour - o			
	D)	1.0 L						
65	Whic	h defect is caused by the			M. G	0567	(0)	
	wood	h defect is caused by due to uncontrolled and n	on-u					e in
	A)	Knot						300
,		Cross grain						
	4.5							
		Warping						
	D)	Shake						
60	D							
90.)	For hi	gh rise buildings, which types of crane are used	£					
	A)]	Derrick crane						
	B) (Overhead gantry crane						
	C)	lower crane					704	
	D) ?	Traveller crane						
State		Control of the second of the s			-		188	

(16)


(20) (A)

7. Wha	t is the duration by which the completion time o	of any activity can be delayed without
A)	ting the start of any succeeding activities?	10 10 10 10 10 10 10 10 10 10 10 10 10 1
	and Hour	
B)	Minimum float	
C) D)	Maximum float Free float	
D,	rec noat	
58. În c	ase of research and development type of activit	y which of the following technique is
mos	t suitable?	thighten at 2
A)	Bar chart	
B)	Graphical evaluation and review technique	
C)	Research evaluation and review technique	
D)	Project evaluation and review technique	
69. Wh	ich of the following pairs are correctly matche	ed?
A)	Grading: Maximizes cement content	
B)	Particle size and texture: Affects workability	
C)	Absorption and surface moisture: Affects n	nix proportions ~
D)	Bulk density: Significant for stability	
1	o potraci glica distillativa pot etti labivitad s	daing the mix design for nevement
	hich property of concrete is considered while	doing the mix design for pavement
-	ncrete?	
A)		
B)		
C		
D		
7 . T	he specific gravity of sandstone is	
Α		
В		
	2) 1.8 to 2.65	(1) (1) (2) (2) (3) (3) (4)
	2.95 to 3.4	O) finglinearing savey
72/	According to IS456:2000, the theoretical valu	e of affective length of a compression
r	nember effectively held in position and restrain other end restrained against rotation but not hel	ed against rotation at one end, and at the
	A) 0.70 l	Page (80) 1
	3) 2.01	
	,	
1	0) 0.50 1	V OP (483)
(20) (4	A) (17)	[P.T.O.

73.	Но	w is the fineness of cement	measured?	
	A)	Volume/Mass		
	B)	Mass/Volume		
	C)	Mass/Area		
	D)	Area/Mass	Assumant float	7 (3
.74.	Cor	nsider the following strengt	ths of concrete	
	1.	Cube strength		2002 TH 1260
	2.	Cylinder strength		
	3.	Split-tensile strength	implical evaluation and review technique	
	4.	Modulus of rupture	recards evaluation and review to during the	
	Wh	nat is the correct sequence in	n increasing order of these strengths?	
	A)	3 4 2 1		
	B)	3,4,1,2	of the following pairs are correctly matched?	
	C)	4,3,2,1	edicing who are restured Affects work ability "	
	D)	4,3,1,2	Secretary and surface moisture the least miss	
			Sult consit as ignificant for stability	
75.	The thro	area under β-distribution c ough	urve is divided into two equal halves by vertica	al ordinate
	A)	Expected time		
	B)	Optimistic time	Emmed sierie compressive strength	
	C)	Most likely time		
	D)	Pessimistic time	Alignotis bao. Algantis armeti	
76.	A su	rvey which is done for fixing	ng the property lines is known as	rient 33
	A)	Cadastral survey	ing the property management	
	B)	Topographical survey		
	C)	City survey		
	D)	Engineering survey		
77.	Wha		B. If magnetic bearing of 39°25' and magnetic d	eclination
	A)	35°4'	g ari blo E son lud n oimagn Issuanda barr Estera ber Lovi o	
	B)	43°46'		
	C)	30°43'		
	D)	48°7'	E0c.0.	(4
(20)	(A)	The state of the s	(18)	(2)(00)

78.	A su and the t	distance between 2 points on the plan draw true distance between the discovered that he used a so	wn to scale of 1 cm cale of 1 cm = 50m	=25m i. Find
	A)	250m		
	B)	500m		
	C)	750m		
	D)	1000m along large and Ris midus of contra		1 388.) 3.
79.	The	e combined correction for curvature and refraction for distar	co 1 lem (in 1	neters).
	A)	0.049	ice of 2.1 km (mm	10001
	B)			
	C)	0.112	(2R)	
	D)	0.483		
	,	0.405	(28)	
80.		of a floor is 200.49m. Staff reading on floor is 1.695 m, revn against the bottom of roof is 3.305. The height of ceiling 6 m 3.305 m	ng is.	Tupside
			Star and block p	
	C)		Rectangular Abi Star and clicula	
	D)	4 49 m	Star and with pu	
81.	Fora	a well-conditioned triangle		
	i.	Angles are <30° and >120°		
	ii.	those angles equal to 46°14'		
	iii.	Angles are >30° and <120° Angles are >30° and <120°	, Notes distactory Mone of these	
		1 - a gual to 56°14'		
	Whi	ore correct.	egenneren of Fig	86. The
		그 그들이 그 그 그들은 그는 그는 그들을 가지 않아 가장 아름다면 하는 것이 되었다.	62.5 m	
	A)	Only iii		
	B)	i and iv		- 6
	C)	Only ii		(0)
	D)	iii and iv		MANAN
(20)		(19)	t	[P.T.O.
(20)	(A)	원보 하는 생님들이 되는 사람들이 되었다면 생각하면 하다 되었다.		

- The departure of 12 m long AB line is 6 m. What is the reduced bearing of line AB in NE quadrant.
 - A) N 60° E
 - N 30° E B)
 - N 45° E
 - D) N 15° E
- 83. For a staff reading, the correction of curvature (C_C) is given by. (d is horizontal distance between station and point along line of site and R is radius of earth)
 - A) $C_c = \frac{1}{7} \left(\frac{d^2}{2R} \right) (+ ve)$
 - B) $C_c = \left(\frac{d^2}{2R}\right)(-ve)$
 - C) $C_c = \left(\frac{d^2}{2R}\right)(+ve)$
 - D) $C_c = \frac{1}{7} \left(\frac{d^2}{2R} \right) (-ve)$
- 84. Road pattern opted for Nagpur Road Plan (Ist 20-year Road Development Plan) is.
 - Star and block pattern A)
 - Rectangular/block pattern B)
 - Star and circular pattern C)
 - Star and grid pattern D)
- If the UI (Unevenness index) of pavement surface is measured to be 352 cm/km, then the pavement is.
 - A) Comfortable
 - B) Just satisfactory even at higher speeds (100 kmph)
 - C) Not satisfactory and cause discomfort even at 50 kmph
 - None of these D)
- The coefficient of friction in longitudinal direction of a highway is given as 0.4. The breaking distance for car moving at a speed of 90 km/h is. (take $g = 10 \text{ m/s}^2$)
 - A) 62.5 m
 - 78.125 m B)
 - C) 60 m
 - D) 70.7 m



- i. $\frac{P}{w} \ge \frac{b}{2h}$
- ii. $f < \frac{b}{2h}$
- iii. $\frac{P}{w} < \frac{b}{2h}$
- iv. $f > \frac{b}{2h}$

Among the above-mentioned two different condition(s), choose correct option.

- A) ii and iii
- B) i and iv
- C) Only ii
- Which one of the fi-dowing is an assumption that is not inherent to unit my anold in (C

88. If the extra-widening required for 2 lane highway at horizontal curve of 225 m radius is 0.91 m, considering wheelbase of 8 m and what is the design speed of vehicle in km/h.

- A) 100
- B) 90
- C) 85
- D) 95

89. If the ruling gradient is 1 in 120 on a particular section of broad gauge and at same time a curve of 4° is situated on this ruling gradient. What should be the allowable ruling gradient.

- A) 1 in 196
- B) 1 in 174
- C) 1 in 163
- D) 1 in 149

90. Following is not a mode of failure in concrete pavement

- A) Pumping failure
- B) Curling failure
- C) Reflection cracking failure
- D) Temperature stresses induced failure

91.	mo	ven that, the volume of atmospheric moisture is 13,000 km ³ and the flow rate of isture from the atmosphere as precipitation is 600,000 km ³ /y. What approximately is value of residence time of global atmospheric moisture?		
	A)	8 days		
	B)	4 days		
	C)	16 days		
	D)	12 days		
92.	If f_0 is the initial infiltration rate and f_0 is the constant rate of infiltration after time 't'. According to Horton's equation the decrease in rate of infiltration from f_0 to f_0 is,			
	A)	Cubic		
	B)	Exponential \$200 do (a nottibaço montifica una bono pre-resono e ora gracia se		
	C)	Logarithmic		
	D)	Linear		
93.	Whi	ch one of the following is an assumption that is not inherent to unit hydrograph model?		
	A)	The excess rainfall has a constant intensity within the effective duration.		

The excess rainfall is not uniformly distributed throughout the whole drainage area. B)

For a given watershed, the hydrograph resulting from a given excess rainfall reflects C) the unchanging characteristics of the watershed.

The base time of the direct runoff hydrograph resulting from an excess rainfall of D) given duration is constant.

According to Muskingum method which is used for handling a variable discharge-storage relationship, if two of its routing equation coefficients are given by, $C_1 = 0.44$, $C_3 = 0.18$. What is the value of C₂?

A) 0.28

B) 0.62

C) 0.31

D) 0.38

The probability that the maximum discharge in a tributary of Narmada River will equal or exceed 8,000 m³/s in any year is approximately 0.195. What is the probability that the maximum discharge will exceed 8,000 m³/s at least once during the next three years?

A) 0.80

B) 0.27

C) 0.48

0.55

(20)(A)

- 96. In a confined aquifer where the flow rate to a well is 1000 m³/day, and observation wells at distances of 100 and 200 metres from the pumping well have depths to the water table of 100-m and 90-m, respectively. The upper surface of the aquifer is 150 m below ground and the aquifer is 50 m in depth. Assuming datum at 200 metres below ground surface, Calculate transmissivity of the confined aquifer. [ln (2) = 0.69]
 - A) 11 m²/day
 - B) 15 m²/day
 - C) 9 m²/day
 - D) 18 m²/day
- Reference evapotranspiration is 8 mm/day in summer. Calculate the evaporation per day in summer from a 300 m long, 2 m wide canal.
 - A) 4.8 m³/day
 - B) 6 m³/day
 - C) 2.4 m³/day
 - D) 0.24 m³/day
- 98. For a channel having parabolic channel section with top width = T and depth = y. The Hydraulic Radius (R) is given by,
 - A) $(8T^2 + 3y^2)/(2T^2y)$
 - B) $(2T^2y)/(8T^2+3y^2)$
- C) $(2T^2y)/(3T^2+8y^2)$
 - D) $(3T^2 + 8y^2)/(2T^2y)$
- Given that the standard deviation (σ) and mean (μ) of rainfall values at existing rain gauge stations is 28 and 110 cm respectively. If the maximum tolerable error in measurements is 5%, calculate the coefficient of variation (C_{ν}) and total no. of rain gauges required.
 - A) 24.85, 26 gauges
 - B) 25.45, 16 gauges
 - C) 24.85, 16 gauges
 - D) 25.45, 26 gauges
- 100. Among the streams listed below, which one receives no input from the base flow?

(23)

- A) Intermittent streams
- B) Ephemeral streams
- C) Perennial streams

(20)(A)

D) Meandering streams

a Free evertail spillway

161. Which one of the following soils has the highest water application efficiency (Irrigation efficiency)? A) Sand Heavy Clay B) Sandy loam C) D) Loam 102. A 120 ha aquifer is affected by drought due to which the water table has dropped by 4.0 m. Assuming porosity and specific retention of the aquifer material to be 35 per cent and 20 percent, respectively, determine the reduction in ground water storage. $64 \times 10^4 \, \text{m}^3$ $48 \times 10^4 \, \text{m}^3$ B) $60 \times 10^4 \, \text{m}^3$ C) D) $72 \times 10^4 \, \text{m}^3$ 403. Match the following, Free overfall spillway The spillway discharge flows in an open a. 1. channel right from the reservoir to the downstream river b. Hydraulic drop is less than about 6 m Ogee spillway 2. C. Advised in case of very high dams, when Cascade spillway 3. the kinetic energy at the toe of the dam is very high. d. Chute spillway The upper part of the spillway surface 4. matches closely with the profile of the lower nappe of a ventilated sheet of water falling freely from a sharp-crested weir.

104.	Assumetu	uming the relative density re of sediment as 970 kg, or rvoir bed.	of a sand particle as 2.5 and estimate the weight of 1 m³ of	dry unit weight of a cubic deposited sediment in the
	A)	1582 kg		
	B)	1428 kg		
	C)	1762 kg	4.01 (18A2	
	D)	1728 kg	with List II (Fixture)	(people) Fradebald Pat
		f.hyt-lff		
105.	Arra	inge in ascending order of	distance from the river.	var in woll g
	A)	Watercourse <minor di<br="">Canal</minor>	stributaries <major distribut<="" td=""><td>aries<branch canal<main<="" td=""></branch></td></major>	aries <branch canal<main<="" td=""></branch>
	B)	Watercourse <minor di<="" td=""><td>stributaries<major distributa<="" td=""><td>ries<main branch<="" canal<="" td=""></main></td></major></td></minor>	stributaries <major distributa<="" td=""><td>ries<main branch<="" canal<="" td=""></main></td></major>	ries <main branch<="" canal<="" td=""></main>
	C)	Main Canal <branch cacourse<="" td=""><td>anal<major distributaries<m<="" td=""><td>inor Distributaries < Water</td></major></td></branch>	anal <major distributaries<m<="" td=""><td>inor Distributaries < Water</td></major>	inor Distributaries < Water
	D)	Main Canal <watercour< td=""><td>rse<major distributaries<mi<="" td=""><td>nor Distributaries< Branch</td></major></td></watercour<>	rse <major distributaries<mi<="" td=""><td>nor Distributaries< Branch</td></major>	nor Distributaries< Branch
			gis due to	este valendo estado de sales
106.	Whi	ch of the following states	ment is correct?	A) Sales of every brings
	A)	The substance used for o	disinfection of water is know	n as coagulant
	В)	Chlorine can be applied	l in the form of chloramines.	C) high adult version fro
	<i>C</i>)	Pre-chlorination increas	ses the bacterial load on filte	the residue so to the control of the
	D)		on the presence of feest out	
107.	If 500 of wa	omg/L and 200 mg/L (Ca ter respectively, then find	aCO ₃ scale) are the total hardi d non-carbonate and carbonat	ness and alkalinity of a sample hardness will be respectively
	A)	300 and 200		A) Oaly (i)
	,	200 and 700		(B) Both (i) and (ii)
	,	700 and 200		Only (ii)
	,			(iii) bas (ii) (i) UA (ii)
	D)	Zero and 500		[P.T.O.
			(25)	

(20) (A)

108. The overflow rate for plain sedimentation tanks is about

- A) 500 to 750 litres/hr/m²
- B) 1000 to 1250 litres/hr/m²
- C) 1250 to 1500 litres/hr/m²
- D) 1500 to 2000 litres/hr/m²

109. Match List-I (Purpose) with List II (Fixture)

	List-I		List-II
a.	To stop flow in reverse direction	1.	Surge arrester
b.	To stop or regulate the flow especially	2.	Butterfly valve
	in large size conduits		
c.	Control of water hammer	3.	Scour valve
d.	To empty or drain the pipeline section	4.	Check valve
A)	a-1 b-2 c-4 d-3		
B)	a-4 b-2 c-1 d-3.	No big	signi pemaning
C)	a-1 b-4 c-2 d-3		
D)	a-3 b-4 c-2 d-1	alvi-ca	Campire Page 1400 to 00 ft

- 110. Alkalinity in natural waters is due to
 - A) Salts of weak bases strong acids
 - B) Drainages from abandoned mines
 - C) Industrial wastes from rayon mills and steel mills
 - D) Photosynthesis of algae in water

111. In order to determine only the presence of fecal coliform organisms and no other microorganisms, the test to be carried out is

- i. Presumptive coliform test
- ii. Confirmed coliform test
- iii. Completed coliform test
- A) Only (i)
- B) Both (i) and (ii)
- C) Only (ii)
- (D) All (i), (ii) and (iii)

112.	Man	ny house sewers discharge is combined into one sewer, which is referred to a	AH SII
	A)	House sewer	is (A
	B)	Lateral sewer	
	C)	Intercepting sewer	
	D)	Submain sewer	
113.	12.0 Its s	0 m \times 1.50 m \times 0.80 m are the dimensions of a grit chamber has a flow of 864 turface loading rate and detention time are, respectively	l m³/hr.
	A)	4800 m ³ /hr/m ² and 4 minute	
	B)	48000 litres/hr/m ² and 10 minutes	
	C)	48 m ³ /hr/m ² and 40 minutes	
	D)	48000 litres/hr/m²and 1 minutes	
114.	Whi	ch of the following is incorrectly matched	
	A)	Mohr method –Ph	
	B)	Winkler method – Dissolved Oxygen	
	C)	Orthotolidine test – Chlorine	
	D)	EDTA method – Hardness 🗸	ed Eu
115.		vated carbon is used for	ed Ĉi
115.	Acti	vated carbon is used for	(A (B
115.	Acti	vated carbon is used for Disinfection	
115.	Acti A) B)	vated carbon is used for Disinfection Removing hardness	
115.	Acti	vated carbon is used for Disinfection	
	ActivA) B) C) D)	vated carbon is used for Disinfection Removing hardness Removing odour Removing corrosiveness which of the available dilution factor sewage may be disposed of without to a water body	reatment
	ActivA) B) C) D)	vated carbon is used for Disinfection Removing hardness Removing odour Removing corrosiveness which of the available dilution factor sewage may be disposed of without to a water body Less than 150	reatment
	ActivA) B) C) D) For vinto a	vated carbon is used for Disinfection Removing hardness Removing odour Removing corrosiveness which of the available dilution factor sewage may be disposed of without to a water body Less than 150 More than 150	reatment
	ActivA) B) C) D) For v into a A) B)	vated carbon is used for Disinfection Removing hardness Removing odour Removing corrosiveness which of the available dilution factor sewage may be disposed of without to a water body Less than 150 More than 150	reatment
	ActivA) B) C) D) For vinto a	vated carbon is used for Disinfection Removing hardness Removing odour Removing corrosiveness which of the available dilution factor sewage may be disposed of without to a water body Less than 150 More than 150 More than 300	reatment
	ActivA) B) C) For v into a A) B) C)	vated carbon is used for Disinfection Removing hardness Removing odour Removing corrosiveness which of the available dilution factor sewage may be disposed of without to a water body Less than 150 More than 150	reatment

- 117. When lead is present in water, it
 - A) Changes odour
 - B) Changes colour
 - C) Changes Taste
 - D) None of the above

118. Match List-I with List - II

List - I

List - II

- a. Hardy Cross method
- 1. Long and narrow pipe
- b. Equivalent Pipe method
- 2. Establishes analysis between flow fluid and flow of current
- c. Circle method
- 3. Algebraic sum of head loss in any closed loop is zero.
- d. Electrical Analysis method
- 4. Domestic supply is neglected and fire demand is considered

O diorolidine rest - Chi

- A) a-3, b-4, c-2, d-1
- B) a-2, b-3, c-4, d-1
- C) a-3, b-1, c-4, d-2
- D) a-3, b-4, c-1, d-2

Disinfection is the process of

- A) Killing all the bacteria
- B) Killing only pathogenic bacteria
- C) Removal of causative organism for disease
- D) Complete destruction of life

220. Statement (I): In super-rate trickling filters, plastic media of 25 to 100 mm size are employed for treatment of waste-water having a very high BOD.

Statement (II): Hydraulic loading rate and organic loading rate for a plastic media are 30 to 90 m³/d/m² and 1000 to 2000 g/d/m³ respectively, which are much higher than in stone media trickling filter.

- A) Both A and R are true and R is the correct explanation of A
- B) Both A and R are true but R is not a correct explanation of A
- C) A is true but R is false
- D) A is false but R is true